

# Ultra mobile PATA/ZIF & CEATA Spinpoint N2



Capacity		80GB	120GB	160GB
PATA/ZIF	3600 RPM class	HS081HA		
	4200 RPM class	HS081HB		HS161JB
CEATA	4200 RPM class		HS12UJQ	HS161JQ

## FEATURES

- MAX.80GB Formatted Capacity Per Disk
- High Speed Digital Singal Processor Based Architecture
- Low Power HDC
- Advanced Power Management Control
- Fluid Dynamic Bearing Spindle Motor Technology
- ATA S.M.A.R.T Compliant
- ATA 28-bit Address Feature Set
- Multi-Burst On-The-Fly Error Correction
- SilentSeek™
- Free Fall Sensor (optional)

### DRIVE CONFIGURATION

Capacity	80 / 120 / 160 GB
Interface	PATA/ZIF, CEATA
Rotational Speed	3600 / 4200 RPM class
Buffer DRAM Size	2M
Byte per Sector	4K

### PERFORMANCE SPECIFICATION

Average Seek time (typical)	13.0 ms
Average Latency	8.3 ms
Media Transfer Rate (Max.)	
3600RPM class	371 Mb/s
4200RPM class	428 Mb/s
Interface Transfer Rate (Max.)	
PATA	66 / 100 MB/s
CEATA	52 MB/s
Drive Reday Time (typical)	2.0 sec

### RELIABILITY SPECIFICATION

Non-recoverable Read Error	1 sector in 10 <sup>13</sup> bits
Controlled Ramp Load/Unload	600,000

### ACOUSTICS

Idle	
80GB	1.6 Bel
120/160GB	1.8 Bel
Performance Seek	
80GB	2.2 Bel
120/160GB	2.4 Bel

### POWER REQUIREMENTS

Voltage	+3.3V ±5%
Spin-up Current (Max.)	400 mA
Seek (typical)	0.8 W
Read/Write (typical)	
80GB	0.9 W
120/160GB	1.0 W
Idle (typical)	0.30 W
Standby (typical)	0.07 W
Sleep (typical)	0.07 W

### ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5 ~ 60 °C
Non-operating	-40 ~ 85 °C
Humidity (non-condensing)	
Operating	8 ~ 90 %
Non-operating	8 ~ 90 %
Linear Shock (1/2 sine pulse)	
Operating, 2ms	600 G
Non-operating, 1ms	1500 G
Vibration	
Operating	0.67 Grms
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-400 to 15,000 m

### PHYSICAL DIMENSION

Height (Max.)	
80GB	5.0 mm
120/160GB	8.0 mm
Width	71.0 mm
Length	54.0 mm
Weight (avg.)	
80GB	48 g
120/160GB	59 g

\* Note : Design and specifications are subject to change without prior notice.

1MB = 1,000,000 Bytes, 1GB = 1,000,000,000 Bytes

Accessible capacity may vary as some OS uses binary numbering system for reported capacity.

CEATA 48-bit Address Feature Set

